



단위: 직경mm / 무게 kg

| 호칭 지름(DN) | D | g | a | b | f | S | C | 수 | d | 볼트호칭 | 무 게 |
|-----------|------|------|------|------|---|------|------|----|----|------|-------|
| 80 | 200 | 133 | 19.0 | 16.0 | 3 | 15.0 | 160 | 4 | 19 | 16 | 3.0 |
| 100 | 220 | 153 | 19.0 | 16.0 | 3 | 15.0 | 180 | 8 | 19 | 16 | 3.3 |
| 125 | 250 | 183 | 19.0 | 16.0 | 3 | 15.0 | 210 | 8 | 19 | 16 | 4.0 |
| 150 | 285 | 209 | 19.0 | 16.0 | 3 | 15.0 | 240 | 8 | 23 | 20 | 4.9 |
| 200 | 340 | 264 | 20.0 | 17.0 | 3 | 16.0 | 295 | 8 | 23 | 20 | 6.8 |
| 250 | 400 | 319 | 22.0 | 19.0 | 3 | 17.5 | 350 | 12 | 23 | 20 | 9.6 |
| 300 | 455 | 367 | 24.5 | 20.5 | 4 | 19.5 | 400 | 12 | 23 | 20 | 12.8 |
| 350 | 505 | 427 | 24.5 | 20.5 | 4 | 19.5 | 460 | 16 | 23 | 20 | 14.1 |
| 400 | 565 | 477 | 24.5 | 20.5 | 4 | 19.5 | 515 | 16 | 28 | 24 | 16.3 |
| 450 | 615 | 527 | 25.5 | 21.5 | 4 | 20.5 | 565 | 20 | 28 | 24 | 18.1 |
| 500 | 670 | 582 | 26.5 | 22.5 | 4 | 21.0 | 620 | 20 | 28 | 24 | 21.8 |
| 600 | 780 | 682 | 30.0 | 25.0 | 5 | 23.0 | 725 | 20 | 31 | 27 | 30.8 |
| 700 | 895 | 797 | 32.5 | 27.5 | 5 | 24.0 | 840 | 24 | 31 | 27 | 40.5 |
| 800 | 1015 | 904 | 35.0 | 30.0 | 5 | 24.5 | 950 | 24 | 34 | 30 | 54.8 |
| 900 | 1115 | 1004 | 37.5 | 32.5 | 5 | 26.5 | 1050 | 28 | 34 | 30 | 64.3 |
| 1000 | 1230 | 1111 | 40.0 | 35.0 | 5 | 28.0 | 1160 | 28 | 37 | 33 | 81.4 |
| 1100 | 1340 | 1218 | 42.5 | 37.5 | 5 | 30.0 | 1270 | 32 | 37 | 33 | 105.0 |
| 1200 | 1455 | 1328 | 45.0 | 40.0 | 5 | 31.5 | 1380 | 32 | 40 | 36 | 120.9 |